



Tapping Fluid

Increases Productivity and Tap Life!

EMUGE Tapping Fluid is an extreme duty drilling and tapping fluid. It does not contain chlorinated solvents and is considered environmentally safe. EMUGE Tapping Fluid is thick like honey and will stick to the tap throughout the tapping operation. Ideal for tapping and drilling stainless steel, carbon steel, inconel, monel, hastalloy, titanium, aluminum and other alloys and exotics.

- Greatly extends tap and drill life
- Reduces torque
- Improves finish and size
- Mild pleasant odor
- Does not contain chlorinated solvents



Typical Analysis

Appearance	Light amber oil
Specific Gravity	1.108
Viscosity @100° F	>900 SUS
Flash Point (PMCC)	415° F
% Petroleum Distillate	None

EMUGE Tapping Fluid

Description	EDP No.
24 x 4 oz. bottles per case	FZ191900.JM321
4 oz. sample bottle	JM320
12 x 16 oz. bottles per case	FZ191900.JM322
4 x 1 gallon bottles per case	FZ191900.JM326
1 x 5 gallon can w/spout	FZ191900.JM324
1 x 55 gallon drum	FZ191900.JM325

Contact Emuge:

1800 Century Drive | West Boylston, MA 01583-2121 | 800.323.3013 | www.emuge.com

